

Fénix Touch Monitor 17"

FÉNIX

17" LCD supports 1280x1024px

Metallic support

Resistive and 3mm tempered glass options

Versatile mounting brackets

Modular architecture for efficient chassis integration

VGA interface/DVI (option)

MSR Card Reader (option)



Specifications

- **I/O Ports** VGA Input: 15 Pins D-Sub x1
DVI Input: 24 Pins DVI-D x1 (option)
- **Plug & Play** VESA DDC 1/2B
Compatible Support
- **OSD Control** Keys: Auto-tune, menu, decrease and increase
Functions: Brightness, contrast, clock, phase,
Position: Horizontal/ Vertical
- **Power Consumption** 30W max
- **Power** Build-in power supply with AC 100~240V
- **Temperature** ~5°C~90°C for desk top
- **Title Angle**
- **Carton Dimensions (LxWxH)** 458mm x 240mm x 451mm
- **Net Weight** 5kg +/- 1



Display

- **LCD Diagonal Size(inch)** 17"
- **Resolution** SXGA (1280x1024)
- **Mode** TN
- **Response Time (ms)** 8
- **Number of Colors** 16.2M
- **View Angle(H/V)** H:150°/V:130°
- **Brightness (cd/m2)(typ.)** 300nits
- **Contrast Ratio (ms)(Typ.)** 500:1
- **Lamp life (hours)** 40,000



Environment

- **Operating Temperature** -0°~45°C
- **Storage Temperature** -20°~60°C for standard LCDs
- **Humidity** 10~90% non-condensing
- **EMC Approved** CE, FCC
- **Safety Approver** ETL/Cus

Touchscreen

- **Type** 5-wire Resistive
- **Thickness** 3mm
- **Resolution** Continuous
- **Light Transmission** >80%
- **Controller Interface** RS-232 or USB
- **Power Consumption** +5V@200mA
- **Touch lifetime (finger)** 35 million times
- **Driver OS Support** DOS, Linux and Windows 95/98/NT/ME/2000/XP/Windows 7/Windows 8